

[http://www.cartft.com/catalog/il/1213]



298.00 EUR

incl. 19% VAT, plus shipping

- DVI + D-SUB-15
- · High brightness!
- · Partly metal case!
- 600 nits!

Support: 800x480 Driver (Windows 7)

New! With digital DVI input!

The MHD700 delivers an impressive 600 cd/m2 light output – a light level that places it at the very top end of the market in terms of brightness. This light output is achieved with no increase in power consumption over previous models. The model is partially wrapped into a metal enclosure, the temperature range is -35°C to 85°C. The contrast ratio is 650:1.

The new MHD700 TFT-Display is the ideal display- and input-unit for your Laptop, CarPC or HTPC. With the touchscreen functionality you easily can control your PC. The briliant VGA-display ensures a maximum readability and sharpness.

The device has integrated Stereo-speakers, a rear camera input and the dimmer button in the front will enable perfect viewing pleasure also during the night.

AC-Adapter for home usage and a car cigarette lighter adapter is included as well as the IR-remote-control unit and the extra long (2,5 meters) All-In-One connector cable.

The MHD700 can be used with any PC/MAC with VGA- (or DVI-) and USB port.

Driver-CD included, compatible with:

- Windows 95/98/ME/NT4/2000/XP/7/8/8.1/10
- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat,Mandrake,...
- Macintosh OS 9.x, 10.x
- DOS,..

| Spezifications | |
|-----------------------|--------------------------|
| Screen size | 7" digital |
| Aspect Ratio | 16:9 wide TFT screen |
| Dot Resolution | 2400x480= 1,152,000 dots |
| Physical Resolution | 800x480 |
| Supported Resolutions | 640x480-1920x1080 |
| Color configuration | RGB stripe |



MHD700 - VGA/DVI 7" TFT - Touchscreen USB - Autodimmer - IR Remote - Audio (600nits , Partly metal enclosure)

[http://www.cartft.com/catalog/il/1213]

| Power input | DC 11-24V |
|----------------------|---|
| Power consumption | max. 8W |
| Video system | 3x Video inputs (PAL/NTSC) |
| | 1x VGA input |
| | 1x DVI input |
| | Display Case : 190x132x34 mm |
| | Display : 158 x 85 mm |
| Video input signal | 1.0Vp-p, composite video |
| Brightness | 650 cd/m ² |
| Contrast | 600:1 |
| Vibration | EC68-2-6 |
| Operating Temperatui | re -30° bis 85°C |
| <i>Features</i> | Full function OSD control (englisch) |
| | Built-in Stereo-speakers |
| | Earphone-Output (rear side) |
| | Automatic switching to rear camera (by signal detection on AV3) |
| | Auto Power On/Off |
| | Autodimmer |
| What is included? | - 7" VGA/DVI Touchscreen TFT with Video/Audio-support |
| | - Infrared Remote Control |
| | - Car dash mounting bracket |
| | - Touchscreen pencil |
| | - VGA/Video/Audio/Touchscreen-cable (all-in-one!) 2,5 meters length |
| | - DVI-cable |
| | - Power Adapter f. EU 230V |
| | - Cigarette Lighter Adapter |
| | - Touchscreen Driver-CD |
| | - Manual |

The display is vibration- and shock-tested (BS EN 61373: 1999).



Displays with $\underline{\text{True-800x480-Support}}$ achieve a pixel accurate view at 800x480@70Hz