

[http://www.cartft.com/catalog/il/1278]



249.00 EUR

incl. 19% VAT, plus shipping

- Fanless!
- Auto Power On/Off!
- e13 certified!
- WLAN/GPS/GPRS!



Support: Drivers (Win) | Drivers (Linux) | GPS/GSM/GPRS Setup [EN]

This MiniPC was especially designed for fleet applications. The Car-PC can be connected directly to the car battery (12V/24V). Based on ignition plus, the PC will start and shutdown.

For a full PC you need in addition:

- 2.5" HDD/SSD or CompactFlash

The PC is completely fanless and is equipped with an Intel Celeron Mobile (M440) 1.83Ghz CPU and 1GB RAM.

Project orders:

The system also is available with other CPUs (eg. T2500/T7400/...). And you can get 2GB RAM. The system also can be shipped without GPS, WLAN and/or GSM/GPRS option. It is also possible to extend warranty time to 3-5 years. Contact us!

Features:

- Fanless
- Intel Sockel P Mobile CPU Support
- Integrated, intelligent Automotive power supply
- 2x RS232
- 2x Gigabit LAN
- DSUB-15 VGA + DVI
- Watchdog
- GPS, WLAN, GSM/GPRS with ext. antennas
- 8bit GPIO
- EMark 13 and vibration/shock tested

279mm W x 176mm D x 67mm H, 2.9kg
Socket M (support Intel Core 2 Duo/Core Duo/Celeron M) [Intel
Celeron-M 1.86Ghz included]
Intel 945GME + Intel ICH7M , 533/667Mhz FSB
1x SO-DDR-2 RAM (up to 2GB 533/667) [1GB RAM included]
Intel GMA 950
1x PCI-104 module slot
Internal USB WLAN module [Included]
Internal RS232 GPRS/GSM module COM3 [Included]
Internal RS232 GPS module COM4 [Included]



FleetPC-3 Car-PC (Intel Celeron-M 1.8Ghz, 1GB RAM, Autostart-Controller, 9-32V Automotive PSU, WLAN, GPS, GPRS) [FANLESS]

[http://www.cartft.com/catalog/il/1278]

OS Support	Windows XP Home/Pro/Embedded, Linux FC 6/7
Vibration	IEC 60068-2-64 5~500Mnz
	2GRMS for CF, 3GRMS for SSD
Shock	IEC 60068-2-27 50G-500m/s ² -11ms
Operating temperature	-20~60°C (with Industrial grade CF)
Certification	CE, FCC class B, EMark 13
I/O	- 2x LAN (Broadcom BCM5787)
	4x RS232 (2x DB9, 2x internal used for GPS+GPRS)
	- 4x USB2.0 (3x external, 1x internal used for WLAN)
	- 8bit GPIO (4 in, 4 out)
	- 1x PS/2
	Mic-In, SPK Out
	- 1x Remote power control
	- 15A Fuse for 12V, 0.5A for 24V
	1x VGA (DSUB-15)
	- 1x DVI
	3x Antenna hole (GPS, GSM/GPRS, WLAN)
Drive bays	1 x Anti-Shock 2.5" HDD bracket (for IDE-44pin or SATA II)
	1 x External CF slot (Type I/II)
Power supply	9~32V DC PSU included (90W max)
	- Fuse design
	- Power on/off retry
	- Adjustable delay time for system OFF by switch
	System on/off by vehicle ignition or remote switch button
	Low power input monitoring, Auto Shutdown
Scope of supply	FleetPC-3 PC with Intel Celeron-M 440 (1.86Ghz), 1GB RAM,
	mounting bracket
	- Quickstart-Guide, DriverCD
	- Remote switch cable
	- Replacement fuse f. 24V
	- HDD bracket and screws
	- SATA data cable, SATA power cable
	- WLAN, GPRS and GPS antennas
	PS/2 Splitter cable
	- 2x mounting-metal brackets
	- ZA Mounting-metal blackets