



Support: 🔁 Specifications | Drivers (Windows) | Dialer Software

The ME906E is a LTE module with NGFF interface, supporting LTE (FDD) B1/B2/B3/B5/B7/B8/B20,Penta-band DC-HSPA+/HSPA+/HSPA/WCDMA for Europe network coverage, low power consumption, Global Navigation Satellite System(GNSS), and European carrier certifications, enabling easier and more flexible design and integration into end devices. In addition, the ME906E supports NGFF features to optimize performance, power consumption, and usability.

ME906E is the ideal choice for Ultrabook, notebook, tablet etc.

Manufacturer	Huawei	
Model	ME906E	
Unlocked	Ready for use with global services. No contract required.	
Network Bands	<ul> <li>LTE (FDD) B1/B2/B3/B5/B7/B8/B20 Quad-band DC-HSPA+/HSPA+/HSPA/UMTS B1/B2/B4/B5/B8 Quad-band EDGE/GPRS/GSM 1900/1800/900/850 MHz</li> </ul>	
Data Speed	GPRS/EDGE: Multi-slot Class 12	
	WCDMA PS: UL (384 kbps)/ DL (384 kbps)	
	DC-HSPA+ :UL (5.76 Mbps)/ DL (42 Mbps)	
	LTE FDD: UL (50 Mbps)/ DL (100 Mbps) @Bandwidth 20M (CAT3)	
	Antenna interfaces x 2	
Interface Power Supply	M.2 Socket 2	
	USB 2.0 interface high speed	
	Power supply	
	UICC interface	
	Supply voltage range:3.135V~4.4V (3.3 V recommended)	
	Normal operation: -10°C to +55°C	
Temp Range	Extended operation: -20°C to +70°C	
	Storage: -40°C to +85°C	
GPS	GNSS: GPS Standalone, A-GPS, GPS XTRA, Glonass	
Dimensions	• 42x30x2.3 mm	



Supported Systems	Windows 7/Windows 8/Android 4.0 or above
	SIM Hotswap
	IPV6
	BodySAR
Special Eastures	Ultrabook feature support(ACT, WiFi Offload , DPTF)
Special Features	Tunable Antenna
	Supporting MO and MT
	Supporting formats of PDU
	Point-to-point and cell broadcast
Package Contents	New Huawei ME906E NGFF Embedded Module.