





1449.00 EUR

incl. 19% VAT, plus shipping

- 1366x768 Multi-Touchscreen!
- Fanless ! IP65 Front !
- Intel Kaby Lake CPU!
- 2x LAN, 2x COM!



Support: Specifications

D151 series is a 15.6" ultra-thin wide-screen fanless Panel PC featuring Intel Kaby Lake ULV Core-i CPU. The distinct aluminum extrusion frame with matte black or silver finish gives the system an understated luxury and elegant look. The series also featuring a bright TFT-LCD with LED backlight display and true flat 10-point projective capacitive multi-touch front panel that's IP65 compliant, along with optional universal snap-in peripherals (MSR, Smart card reader, NFC/ RFID reader, barcode scanner, camera), making it perfect for diversified self-service and interactive signage markets including retail, hospitality, gaming, corporate, healthcare and light



## Mitac D151-11KS [Intel i3-7100U] 15.6" Panel PC (1366x768, Multi-Touchscreen, PD11KS 3.5-SBC Kaby Lake, IP65 Front, Fanless)

[http://www.cartft.com/catalog/il/2399]

industrial applications.

Model Name D151-11KS
Motherboard PD11KS

Intel Kaby Lake-U i3-7100U with integrated graphics (Compatible Processor with Skylake 3955U / i3-6100U / i7-6600U and Kabylake

3965U / i5-7300U / i7-7600U)

System Memory 2 x DDR4 SO-DIMM, support up to 32GB

Processor Graphic Intel® HD Graphics 620 (Graphics Burst Frequency 1.10GHz)

Touch Display

LCD Size 15.6" TFT LCD with LED Backlight 50000 lifetime

Brightness500nitsResolution1366 x 768Viewing Angle170°/160°

Touch Screen True-flat 10 points projective capacitive touch

Storage

HDD/SSD 1 x 2.5 internal HDD/SSD bay

Expansion

Extension slots

M.2 (2230) : 1 x M.2 E key for wireless network

MiniPCle : 1 x full length mPCle supporting mSATA

4

I/O Ports

USB3.0

DC Jack 1 (8V to 24V wide-range voltage input)

GigaLAN (10/100/1000) 2

Display-Port (support 4K 3840x2160)

Display-Port (support 4K 3840x2160)

Audio jack 1 x combo jack w/mic-in and line-out

HDMI-out

Serial Port 1 x RS-232, 1 x RS-232/422/485

Thermal Solution

Thermal Solution Fanless

Audio

Stereo Speaker 2W x 2

Power

Power Supply 65W/19V

Certification

EMC & Safety CE/FCC Class A

Environment

Operating Temperature  $0^{\circ}\text{C} \sim 40^{\circ}\text{C} (32^{\circ}\text{F} \sim 104^{\circ}\text{F})$ Storage Temperature  $-20^{\circ}\text{C} \sim 60^{\circ}\text{C} (-4^{\circ}\text{F} \sim 140^{\circ}\text{F})$ 

Relative Humidity 10%~95% @40°C non-condensing

Front Panel Protection IP65 Compliant
Dimension 400 x 250 x 44 (mm)
Weight 4.8kg (10.58 lb)

Mounting 100mm x 100mm VESA

Operating System win10, linux support by request