[http://www.cartft.com/catalog/il/2400]





## 1689.00 EUR

incl. 19% VAT, plus shipping

- 1366x768 Multi-Touchscreen!
- Fanless ! IP65 Front !
- Intel Kaby Lake CPU!
- 2x LAN, 2x COM!



Support: Specifications

D151 series is a 15.6" ultra-thin wide-screen fanless Panel PC featuring Intel Kaby Lake ULV Core-i CPU. The distinct aluminum extrusion frame with matte black or silver finish gives the system an understated luxury and elegant look. The series also featuring a bright TFT-LCD with LED backlight display and true flat 10-point projective capacitive multi-touch front panel that's IP65 compliant, along with optional universal snap-in peripherals (MSR, Smart card reader, NFC/ RFID reader, barcode scanner, camera), making it perfect for diversified self-service and interactive signage markets including retail, hospitality, gaming, corporate, healthcare and light



## Mitac D151-11KS [Intel i5-7300U] 15.6" Panel PC (1366x768, Multi-Touchscreen, PD11KS 3.5-SBC Kaby Lake, IP65 Front, Fanless)

[http://www.cartft.com/catalog/il/2400]

industrial applications.

Model Name D151-11KS Motherboard PD11KS

Intel Kaby Lake-U i3-7100U with integrated graphics (Compatible Processor with Skylake 3955U / i3-6100U / i5-6300U / i7-6600U and Kabylake

3965U / i5-7300U / i7-7600U)

2 x DDR4 SO-DIMM, support up to 32GB System Memory

Processor Graphic Intel® HD Graphics 620 (Graphics Burst Frequency 1.10GHz)

Touch Display

LCD Size 15.6" TFT LCD with LED Backlight 50000 lifetime

**Brightness** 500nits 1366 x 768 Resolution Viewing Angle 170°/160°

Touch Screen True-flat 10 points projective capacitive touch

Storage

HDD/SSD 1 x 2.5 internal HDD/SSD bay

Expansion

M.2 (2230): 1 x M.2 E key for wireless network Extension slots MiniPCle: 1 x full length mPCle supporting mSATA

**Fanless** 

I/O Ports

DC Jack 1 (8V to 24V wide-range voltage input)

USB3.0 4 2 GigaLAN (10/100/1000)

Display-Port (support 4K 3840x2160) 1

Audio jack 1 x combo jack w/mic-in and line-out

HDMI-out

Serial Port 1 x RS-232, 1 x RS-232/422/485

Thermal Solution

Thermal Solution

2W x 2 Stereo Speaker

Power

Audio

**Power Supply** 65W/19V

Certification

**EMC & Safety** CE/FCC Class A

Environment

**Operating Temperature** 0°C ~ 40°C (32°F~104°F) -20°C ~ 60°C(-4°F~140°F) Storage Temperature

Relative Humidity 10%~95% @40°C non-condensing

Front Panel Protection IP65 Compliant Dimension 400 x 250 x 44 (mm) Weight 4.8kg (10.58 lb)

Mounting 100mm x 100mm VESA Operating System win10, linux support by request