

469.00 EUR

incl. 19% VAT, plus [shipping](#)

- JBC390F541WXX-19-B



- Intel® Bay Trail SoC Processor
- 1 \* SO-DIMM DDR3L 1333MHz up to 8GB
- 3 \* USB2.0, 1 \* USB3.0, 1 \* COM, 1 \* VGA, 1 \* HDMI, 2 \* RJ45, 1 \* MIC, 1 \* Line out
- Product Dimension : 185 x 165 x 48 mm
- DC-12V\_5A\_60W Lockable Adapter

MB Model	- JNF541-1900					
Part No	No Expansion	8 LAN	8 COM	16-bits GPIO	32-bits GPIO	4 USB 3.0
	-	-	-	-	-	-
	HBJC390F541XX-1900-B	HBJC390F541AA-1900-B	HBJC390F541CC-1900-B (non-WIFI)	HBJC390F541XG-1900-B	HBJC390F541GG-1900-B	HBJC390F541XU-1900-B
	-	-	-	-	-	-
	HBJC390F541WXX-1900-B (Wifi)	HBJC390F541WAA-1900-B (Wifi)	HBJC390F541WCC-1900-B (Wifi)	HBJC390F541WXC-1900-B (Wifi)	HBJC390F541WGG-1900-B (Wifi)	HBJC390F541WXU-1900-B (Wifi)
	4 COM+4 LAN	4 COM+4 USB3.0	4 LAN+4 USB3.0	4 COM+16-bits GPIO	4 LAN+16-bits GPIO	16-bits GPIO+4 USB 3.0
-	-	-	-	-	-	
HBJC390F541CA-1900-B	HBJC390F541CU-1900-B	HBJC390F541AU-1900-B	HBJC390F541CG-1900-B	HBJC390F541AG-1900-B	HBJC390F541GU-1900-B	
-	-	-	-	-	-	
HBJC390F541WCA-1900-B (Wifi)	HBJC390F541WCU-1900-B (Wifi)	HBJC390F541WAU-1900-B (Wifi)	HBJC390F541WCG-1900-B (Wifi)	HBJC390F541WAG-1900-B (Wifi)	HBJC390F541WGU-1900-B (Wifi)	
BIOS	- AMI EFI Flash ROM					
CPU/Chipset	- Intel® Bay Trail J1900 SoC Processor					
Memory	- 1 * DDR3L-1066/1333 SO-DIMM up to 8GB					
Storage	- 1 * 2.5" SATA drive bay (only support 2.5" HDD with a height ≤ 10mm) - 1 * Full-size mSATA/Mini-PCI Express shared slot					
Network	- 2 * Intel i211AT Gigabit LAN - 1 * Half-size Mini-PCIe slot (802.11 b/g/n + BT 4.0 installed in WiFi model) - 1 * SIM Card Slot					

Rear Panel I/O	<ul style="list-style-type: none"> <li>- 1 * USB 3.0, 3 * USB 2.0</li> <li>- 1 * HDMI, 1 * VGA</li> <li>- 2 * RJ45</li> <li>- 1 * Line-out, 1 * MIC-in</li> <li>- 1 * COM (Support RS232/422/485)</li> <li>- 2 * Antenna holes ( WiFi only)</li> <li>- Lockable DC-In jack</li> </ul>
Front Panel I/O	<ul style="list-style-type: none"> <li>- 1 * Power button + LED</li> <li>- 1 * HDD LED</li> <li>- COM (Expansion Module)</li> <li>- Intel Gigabit LAN (Expansion Module, support RS232/422/485)</li> <li>- USB3.0 (Expansion Module)</li> <li>- 16-Bits GPIO (Expansion Module)</li> </ul>
Power Source	<ul style="list-style-type: none"> <li>- 60W AC-DC Adapter / DC12V-5A</li> <li>- AC 90~240V input</li> </ul>
Compliance	<ul style="list-style-type: none"> <li>- CE, FCC, RoHS, ErP Ready</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>- Operating temperature: 0 ~ 50° C</li> <li>- Storage Temperature: -10 ~ 70° C</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>- 185 (W) x 165 (D) x 48 (H) mm</li> </ul>
Packing	<ul style="list-style-type: none"> <li>- Net Weight: 2.4KG</li> <li>- Gross Weight: 3.4KG</li> <li>- Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm</li> </ul>
OS Support	<ul style="list-style-type: none"> <li>- Windows 7, Windows 8.1, Windows 10, Linux</li> </ul>
Warranty	<ul style="list-style-type: none"> <li>- 2 Years limited warranty</li> </ul>