



369.00 EUR
incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- HB368F21 !

- Intel Elkhart Lake SoC Processor
- 1* DDR4 3200MHz SO-DIMM up to 32GB
- 2* USB3.1 (Gen.2), 4* USB2.0, 2* RJ45, 1* Audio (MIC + Line-out), 1* Line-IN, 3* DP, 2* COM, 1* GPIO
- 160.2*106*27 mm
- DC12V_40W Adapter
- Support TPM2.0 (option)

| | | |
|--------------------|--|--|
| Model | - HB368F21-6210-S (non-WiFi) - HB368F211-6210-S (WiFi) | |
| CPU/Chipset | - Intel® Elkhart Lake SoC Processor(N6210, TDP 6.5W) | |
| BIOS | - AMI Flash ROM | |
| Memory | - 1* DDR4 3200MHz SO-DIMM up to 32GB | |
| Network | - 2* Realtek RTL8119I GbE | |
| Graphics | - Intel® HD Graphics, shared memory - 3* DP (Max Resolution: 4096x2160@60Hz) - Support Triple Displays | |
| Storage | - 1* M.2 M-key (2242/2280, PCIe Gen.3 x2/SATA interface) support NVME - 32GB eMMC onboard (option) | |
| Expansion | - 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface) - 1* M.2 B-key (3042, USB3.0 interface) | |
| Rear Panel I/O | - 2* RJ45 - 1* DC in (Lockable) | |
| Front Panel I/O | - 1* Power button + Power LED - 4* USB2.0 - 1* Audio(Line out+MIC) - 1* Line in - 3* DP | |
| Internal Connector | - SIM Card Holder | |

| | |
|--------------|--|
| Power Source | - Adapter : AC 90~240V input / DC12V_40W output - MB : DC12~36V input |
| Compliance | - CE, FCC, LVD, RoHS, ErP Ready |
| Dimensions | - System: 160.2 (W) x 106 (D) x 27 (H) mm - Net Weight: 0.61KG: Gross Weight: 1.12KG |
| Temperature | - Operating Temperature: -20 ~ 60° C (Under the condition of using M.2 interface SSD) - Storage Temperature: -20 ~ 60° C - Humidity: 10% ~ 90% RH @40°C (non-condensing) |
| OS Support | - Windows 11, Linux |