

[http://www.cartft.com/catalog/il/385]



999.00 EUR incl. 19% VAT, plus shipping



Support: Device Specification | AMD G-T56N Benchmark | Manual [EN] | Drivers (Windows) | Internal GPS Module |
Drivers (GPS)

This MiniPC was especially designed for fleet applications. The Car-PC can be connected directly to the car battery (12V/24V). Based on ignition plus, the PC will start and shutdown.

For a full PC you need in addition:

- 2.5" HDD/SSD or CompactFlash

The PC is completely fanless and is equipped with an AMD G-T56N 2x1.6GHz CPU and 2GB RAM.

Available additional modules:

The PC comes with 4x antenna-output and 3x Mini-PCle slots.

We recommend these modules:

- HSPA / UMTS / EDGE Mini-PCIe Modem (Huawei EM770W)
- Wireless LAN / Bluetooth Mini-PCI Express [Qcom Combo]

Features:

- Fanless
- AMD G-T56N Dual Core CPU
- AMD Radeon HD 6320 Graphics
- GPS (Atheros Chipsatz)
- 4x Channel Video Input
- 3x RS232



FleetPC-5-VID Mobile DVR Car-PC (AMD G-T56N 2x1.65Ghz, 2GB RAM, Autostart-Controller, 9-36V Automotive PSU, GPS, 4x Channel Video) [FANLESS]

[http://www.cartft.com/catalog/il/385]

- 2x Gigabit LAN
- DVI-I + DSUB-15 VGA
- Watchdog
- Prepared for GPS, WLAN, GSM/GPRS with ext. antennas
- 2 x DI / 2 x DO with Relay 12V / 100mA
- Vibration/shock tested

For FleetPC-5 we offer an direct connector cable for our TFT-dispays.

Mobile DVR Specification Video Input 4 Channels (4 x BNC Connectors) Video Recording Total 120FPS (NTSC), 100FPS (PAL)@D1 Real-Time Total 120FPS (NTSC), 100FPS (PAL)@D1 Video Display NTSC PAL 720x576x25FPS 720x480x30FPS 704x480x30FPS 704x576x25FPS 640x480x30FPS 640x576x25FPS 720x240x30FPS 720x288x25FPS Resolution Format (S/W MPEG4 or S/W H.264) 704x240x30FPS 704x288x25FPS 640x240x30 360x288x25 360x240x30 360x288x25 350x240x30 352x288x25 320x240x30 320x288x25 Audio Input 1 Channel Audio Format MONO / 8 ~16BITS / 8000~48000HZ Software SDK for Windows XP, 7/8, Linux 2.6.20 or Higher **PC Specification** Dimensions / Weight 235mm W x 155mm D x 55mm H, 1.5kg CPU AMD G-T56N Dual Core 2x 1.65GHz Chipset / FSB AMD A55E Controller Hub RAM 2x SO-DDR-3 RAM (up to 8GB 1333Mhz) [1x 2GB RAM included] Graphics AMD Radeon HD 6320 **GPS** Locosys LS26050 - 3x Mini-PCIe (1x occupied by GPS, 1x occupied by Video-card) Expansion Windows XP Home/Pro/Embedded, Windows 7/8, Linux **OS Support** MIL-STD-810F Vibration & Shock Operating temperature -30~70°C (with SSD) CE, FCC, eMark (2009/19/EC, CISPR 25:2008, ISO 7637-2:2004), Certification Railway EN50155 - 2x Gigabit LAN (Realtek RTL8111E) - 3x RS232 (2x with RS-422/485) - 4x USB2.0 - GPIO port (2in, 2out, with Relay 12V/100mA) I/O - SPK Out - 1x DVI - 1x Video-Input connector - 4x SMA Antenna hole (for eg. GPS, GSM/GPRS/3G, WLAN,

Bluetooth)

mounting

1 x 2.5" SATA HDD/SSD drive bay

- Power off Delay Time Setting by Software, Default 5min

- FleetPC-5 PC with AMD G-T56N (2x1.6Ghz), 2GB RAM,

9~32V DC PSU included

- Backup Battery Kit (optional)

Drive bays

Power supply

Scope of supply



FleetPC-5-VID Mobile DVR Car-PC (AMD G-T56N 2x1.65Ghz, 2GB RAM, Autostart-Controller, 9-36V Automotive PSU, GPS, 4x Channel Video) [FANLESS]

[http://www.cartft.com/catalog/il/385]

- 1x Pigtail + antenna for GPS
- 1x Video-Input-cable