



164.00 EUR  
incl. 19% VAT, plus [shipping](#)

- HDMI !
- HDTV !

- VIA CX700M Single chipset Technology
- Support Front Side Bus 533MHz
- Support 2 Serial ATA 2 Devices with RAID 0, 1
- Support PCI 120-Pin Adapter Conn. With Expansion Daughter-boards
- Gigabit Ethernet LAN Supported
- 6 Channel HD Audio CODEC
- VIA VT6307 IEEE1394a Controller
- VIA VT1622A TV Encoder
- 17 x 17CM Mini-ITX Form Factor

<b>Form Factor</b>	Mini-ITX Express Motherboard
<b>CPU</b>	VIA C7 1.5GHZ CPU (12W)
<b>Memory</b>	1 * 240-pin DIMM Sockets for DDR2 533 up to 1 GB
<b>Chipset</b>	VIA CX700M Single Chipset
<b>Power Management</b>	ACPI S3 Compliant ,supports power saving mode
<b>PCI enhanced IDE</b>	2* Ultra DMA 133 / 100 / 66 IDE Devices Support
<b>Serial ATA Interface</b>	2 Serial ATA2 HDDs with RAID 0, 1 Function Support
<b>VGA Interface</b>	VIA Unichrome Pro II
<b>Video Memory</b>	Share Memory up to 128MB
<b>Audio Interface</b>	VIA VT1708A 6-Channel HD Audio CODEC
<b>LAN Interface</b>	VIA VT6122 10 / 100 / 1000 PCI LAN
<b>Extended Interface</b>	1 * 32-bit PCI Slot 1 * PCI 120-Pin Adapter Connector with Expansion Daughter Boards
<b>Internal I/O Port</b>	2 * High Speed USB Connectors for 4 USB 2.0 Ports 1 * CPU Smart Fan Connector, 2 * Chassis Fan Connectors 2 * 9-Pin COM Port Connector 1 * CD / AUX Audio in & SPEAK Out 1 * HDTV Out Connector 1 * IrDA (SIR) 1 * 6-pin Video Input Pin-header 1 * PCI 120-Pin Adapter Conn.

<b>External I/O Port</b>	2 * High Speed USB Connectors @ 480 M-bit / s 1 * D-Sub 15-pin VGA Connector 1 * HDMI Port 1 * PS / 2 Mouse & 1 * PS/2 Keyboard 1 * RJ45 Connector 1 * Audio I / O 1 * IEEE 1394a Connector
<b>BIOS</b>	Award 4 MB Flash ROM
<b>Power Requirement</b>	Standard 24-Pin ATX Power supply
<b>Dimension</b>	170mm x 170mm